

Buffalo Utility S2-2 Chain Technical Specification

Colour Black
with silver decals



Frameset

- Frame Rear-facing horizontal dropout, 130 OLD, carbon steel
- Fork 1" threaded with internally tapered steerer, carbon steel
- Sizes 19", universal fit with dipping top tube
- Unisex

Wheels

- Hubs Rear, threaded, 125 OLD
- Rims 26", 36h, aluminium, box section durable
- nylon rim strip
- Spokes 13G high-carbon steel, 255mm
- Spoke pattern 3-cross
- Tires Kenda Buffalo, 26 x 1.95", anti-puncture layer
- Tubes 1.2mm Butyl, schrader valve

Frameset

- Frame Rear-facing horizontal dropout, 130 OLD, carbon steel
- Fork 1" threaded with internally tapered steerer, carbon steel
- Sizes 19", universal fit with dipping top tube
- Unisex

Extras

- Mudguards Increased tyre clearance with flares steel
- Carrier Steel, rated to 100kg, 142 OLD steel
- Stand Locking centre stand, steel
- Reflectors Attached to spokes and rear mudguard
- Accessories Bell, lock, pump, mini-tool, tyre lever

Wheels

- Hubs Rear, threaded, 125 OLD
- Rims 26", 36h, aluminium, box section durable
- nylon rim strip
- Spokes 13G high-carbon steel, 255mm
- Spoke pattern 3-cross
- Tires Kenda Buffalo, 26 x 1.95", anti-puncture layer
- Tubes 1.2mm Butyl, schrader valve

Drivetrain

- Freewheel 2 speed drivetrain, 19/18T
- Crank Square taper, 45/27T, 170mm steel
- Pedals 9/16" thread, nylon body, cold forged spindle
- Chains 1/2" x 1/8" single speed with quick link, inboard 100 links, outboard 110 links
- Bottom Bracket Sealed cartridge, square taper, 113mm spindle

Cockpit

- Saddle Reinforced base and rails, UV-resistant cover
- Seat post 25.4mm x 250mm, steel
- Handlebar 25.4mm clamp, 600mm width, 20mm rise, 6 degree sweep, steel
- Grips PVC with reinforced ends
- Stem 60mm reach, 15-degree rise, 200mm quill length, 40mm clamp width, steel
- Headset JIS 1" threaded, steel
- Brake set Front & rear caliper brake
- Brake lever Steel core with plastic cover